

## PRODUKTINFORMATION

**TEKNISK INFORMATION 020-75 80 20    ORDERTEL 020-75 80 00    ORDERFAX 020-75 80 10**  
**TECHNICAL INFORMATION +46 8 580 941 15    ORDERPHONE +46 8 580 941 01    ORDERFAX +46 8 580 941 11**  
— Vi reserverar oss mot fel samt förbehåller oss rätten till ändringar utan föregående meddelande —

### ELFA artikelnr.

Antal sidor: 07


70-053-09 BZX55/C2V4 zenerdiod  
70-053-17 BZX55/C2V7 zenerdiod  
70-053-25 BZX55/C3V0 zenerdiod  
70-053-33 BZX55/C3V3 zenerdiod  
70-053-41 BZX55/C3V6 zenerdiod  
70-053-58 BZX55/C3V9 zenerdiod  
70-053-66 BZX55/C4V3 zenerdiod  
70-053-74 BZX55/C4V7 zenerdiod  
70-053-82 BZX55/C5V1 zenerdiod  
70-053-90 BZX55/C5V6 zenerdiod  
70-054-08 BZX55/C6V2 zenerdiod  
70-054-16 BZX55/C6V8 zenerdiod  
70-054-24 BZX55/C7V5 zenerdiod  
70-054-32 BZX55/C8V2 zenerdiod  
70-054-40 BZX55/C9V1 zenerdiod

70-054-57 BZX55/C10 zenerdiod  
70-054-65 BZX55/C11 zenerdiod  
70-054-73 BZX55/C12 zenerdiod  
70-054-81 BZX55/C13 zenerdiod  
70-054-99 BZX55/C15 zenerdiod  
70-055-07 BZX55/C16 zenerdiod  
70-055-15 BZX55/C18 zenerdiod  
70-055-23 BZX55/C20 zenerdiod  
70-055-31 BZX55/C22 zenerdiod  
70-055-49 BZX55/C24 zenerdiod  
70-055-56 BZX55/C27 zenerdiod  
70-055-64 BZX55/C30 zenerdiod  
70-055-72 BZX55/C33 zenerdiod  
70-055-80 BZX55/C36 zenerdiod  
70-055-98 BZX55/C39 zenerdiod

## Silicon Epitaxial Planar Z-Diodes

### Features

- Very sharp reverse characteristic
- Low reverse current level
- Very high stability
- Low noise
- Available with tighter tolerances



94 9367

### Applications

Voltage stabilization

### Absolute Maximum Ratings

$T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Type	Symbol	Value	Unit
Power dissipation	$l=4\text{mm}, T_L=25^\circ\text{C}$		$P_V$	500	mW
Z-current			$I_Z$	$P_V/V_Z$	mA
Junction temperature			$T_j$	175	$^\circ\text{C}$
Storage temperature range			$T_{\text{stg}}$	-65...+175	$^\circ\text{C}$

### Maximum Thermal Resistance

$T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Symbol	Value	Unit
Junction ambient	$l=4\text{mm}, T_L=\text{constant}$	$R_{\text{thJA}}$	300	K/W

### Electrical Characteristics

$T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Type	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_F=200\text{mA}$		$V_F$			1.5	V

# BZX55C...


Vishay Telefunken




Type	V <sub>Znom</sub>	I <sub>ZT</sub> for	V <sub>ZT</sub> <sup>1)</sup> and	r <sub>zjT</sub>	r <sub>zjK</sub> at	I <sub>ZK</sub>	I <sub>R</sub> and I <sub>R</sub> <sup>2)</sup> at	V <sub>R</sub>	TK <sub>VZ</sub>	
BZX55C...	V	mA	V	Ω	Ω	mA	μA	μA	V	%/K
2V4	2.4	5	2.28 to 2.56	< 85	< 600	1	< 50	< 100	1	-0.09 to -0.06
2V7	2.7	5	2.5 to 2.9	< 85	< 600	1	< 10	< 50	1	-0.09 to -0.06
3V0	3.0	5	2.8 to 3.2	< 85	< 600	1	< 4	< 40	1	-0.08 to -0.05
3V3	3.3	5	3.1 to 3.5	< 85	< 600	1	< 2	< 40	1	-0.08 to -0.05
3V6	3.6	5	3.4 to 3.8	< 85	< 600	1	< 2	< 40	1	-0.08 to -0.05
3V9	3.9	5	3.7 to 4.1	< 85	< 600	1	< 2	< 40	1	-0.08 to -0.05
4V3	4.3	5	4.0 to 4.6	< 75	< 600	1	< 1	< 20	1	-0.06 to -0.03
4V7	4.7	5	4.4 to 5.0	< 60	< 600	1	< 0.5	< 10	1	-0.05 to +0.02
5V1	5.1	5	4.8 to 5.4	< 35	< 550	1	< 0.1	< 2	1	-0.02 to +0.02
5V6	5.6	5	5.2 to 6.0	< 25	< 450	1	< 0.1	< 2	1	-0.05 to +0.05
6V2	6.2	5	5.8 to 6.6	< 10	< 200	1	< 0.1	< 2	2	0.03 to 0.06
6V8	6.8	5	6.4 to 7.2	< 8	< 150	1	< 0.1	< 2	3	0.03 to 0.07
7V5	7.5	5	7.0 to 7.9	< 7	< 50	1	< 0.1	< 2	5	0.03 to 0.07
8V2	8.2	5	7.7 to 8.7	< 7	< 50	1	< 0.1	< 2	6.2	0.03 to 0.08
9V1	9.1	5	8.5 to 9.6	< 10	< 50	1	< 0.1	< 2	6.8	0.03 to 0.09
10	10	5	9.4 to 10.6	< 15	< 70	1	< 0.1	< 2	7.5	0.03 to 0.1
11	11	5	10.4 to 11.6	< 20	< 70	1	< 0.1	< 2	8.2	0.03 to 0.11
12	12	5	11.4 to 12.7	< 20	< 90	1	< 0.1	< 2	9.1	0.03 to 0.11
13	13	5	12.4 to 14.1	< 26	< 110	1	< 0.1	< 2	10	0.03 to 0.11
15	15	5	13.8 to 15.6	< 30	< 110	1	< 0.1	< 2	11	0.03 to 0.11
16	16	5	15.3 to 17.1	< 40	< 170	1	< 0.1	< 2	12	0.03 to 0.11
18	18	5	16.8 to 19.1	< 50	< 170	1	< 0.1	< 2	13	0.03 to 0.11
20	20	5	18.8 to 21.2	< 55	< 220	1	< 0.1	< 2	15	0.03 to 0.11
22	22	5	20.8 to 23.3	< 55	< 220	1	< 0.1	< 2	16	0.04 to 0.12
24	24	5	22.8 to 25.6	< 80	< 220	1	< 0.1	< 2	18	0.04 to 0.12
27	27	5	25.1 to 28.9	< 80	< 220	1	< 0.1	< 2	20	0.04 to 0.12
30	30	5	28 to 32	< 80	< 220	1	< 0.1	< 2	22	0.04 to 0.12
33	33	5	31 to 35	< 80	< 220	1	< 0.1	< 2	24	0.04 to 0.12
36	36	5	34 to 38	< 80	< 220	1	< 0.1	< 2	27	0.04 to 0.12
39	39	2.5	37 to 41	< 90	< 500	0.5	< 0.1	< 5	30	0.04 to 0.12
43	43	2.5	40 to 46	< 90	< 600	0.5	< 0.1	< 5	33	0.04 to 0.12
47	47	2.5	44 to 50	< 110	< 700	0.5	< 0.1	< 5	36	0.04 to 0.12
51	51	2.5	48 to 54	< 125	< 700	0.5	< 0.1	< 10	39	0.04 to 0.12
56	56	2.5	52 to 60	< 135	< 1000	0.5	< 0.1	< 10	43	0.04 to 0.12
62	62	2.5	58 to 66	< 150	< 1000	0.5	< 0.1	< 10	47	0.04 to 0.12
68	68	2.5	64 to 72	< 200	< 1000	0.5	< 0.1	< 10	51	0.04 to 0.12
75	75	2.5	70 to 79	< 250	< 1500	0.5	< 0.1	< 10	56	0.04 to 0.12

1) Tighter tolerances available on request:      2) at T<sub>j</sub> = 150°C  
 BZX55A... ± 1% of V<sub>Znom</sub>  
 BZX55B... ± 2% of V<sub>Znom</sub>  
 BZX55F... ± 3% of V<sub>Znom</sub>


**Characteristics** ( $T_j = 25^\circ\text{C}$  unless otherwise specified)




95 9611  
Figure 1. Thermal Resistance vs. Lead Length




95 9599  
Figure 4. Typical Change of Working Voltage vs. Junction Temperature




95 9602  
Figure 2. Total Power Dissipation vs. Ambient Temperature




95 9600  
Figure 5. Temperature Coefficient of  $V_Z$  vs. Z-Voltage



95 9598  
Figure 3. Typical Change of Working Voltage under Operating Conditions at  $T_{amb} = 25^\circ\text{C}$




95 9601  
Figure 6. Diode Capacitance vs. Z-Voltage




95 9605

Figure 7. Forward Current vs. Forward Voltage




95 9607

Figure 9. Z-Current vs. Z-Voltage




95 9604

Figure 8. Z-Current vs. Z-Voltage



95 9606

Figure 10. Differential Z-Resistance vs. Z-Voltage



95 9603

Figure 11. Thermal Response


**Dimensions in mm**



technical drawings  
 according to DIN  
 specifications

94 9366

Standard Glass Case  
 54 A 2 DIN 41880  
 JEDEC DO 35  
 Weight max. 0.3 g





## Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

**Vishay Semiconductor GmbH** has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

**Vishay Semiconductor GmbH** can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

**We reserve the right to make changes to improve technical design and may do so without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay-Telefunken products for any unintended or unauthorized application, the buyer shall indemnify Vishay-Telefunken against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
Telephone: 49 (0) 7131 67 2831, Fax number: 49 (0) 7131 67 2423